


DESCRIPTION:

DSPL RFID UHF Metallic Tags Model: **DS-UITMT** operates effectively with a very good read range, especially when attached to IT assets. It is an apt choice to monitor the Tracking and movement of Laptops, Servers, and Electronic Assets. 3M Adhesive tape can also be provided for easy attachment. Flexible Read/Write Range (reader dependent).

RFID IT TAG



FEATURES:

- Operates effectively with a very good read range, especially when attached to IT Assets.
- Rugged construction for high durability
- Can also be provided with 3M Adhesive tape for easy attachment.
- Flexible Read/Write Range (reader dependent).

TECHNICAL SPECIFICATIONS:

Technology / Frequency	UHF/ FCC: 902-928MHz ETSI: 865-868MHz ASIA: 950-956MHz
Protocol	EPC Class 1 Gen2
Housing Dimensions	38.5 x 14 x 3.5 mm
Chip	ALIEN HIGGS 3
Operating Frequency	865-868MHz, (902-928MHz also available on request)
Operating Mode	Passive
EPC Memory	96 bit extendable up to 480 bits
User Memory	512Bits
Operating Temperature	-40 °C/ + 80 °C
Material	ABS, Polyester
Colour	White with Black/White with Blue
Weight	2g

PRODUCT USE IN THE SECTORS



ASSET TRACKING **EXPRESS DELIVERY** **LOGISTICS** **WAREHOUSE** **MANUFACTURING**

