

DESCRIPTION:

DSPL RFID UHF Windshield Tag Model No. **DS-WINDST** is a tamper-proof tag and can be easily attached with self-adhesive tape. It is a flexible tag and operates effectively with a read range of over 8-10 m when attached inside of the vehicles' windshield. It can be used in electronic toll collection applications, transports systems & vehicle identification

RFID WINDSHIELD TAG



FEATURES:

- Excellent Read Range of up to 15 mt.
- 3M high quality adhesive.
- Tamper evident from all sides.
- Waterproof and Chemical resistant.
- UV resistant and fade proof printing material.
- It can be customized for printing barcode, text, logo etc.

TECHNICAL SPECIFICATIONS:

Technology / Frequency	UHF 865-867MHz
Protocol	EPC Class 1 Gen 2; ISO 18000-6C protocol compliant
Chip	Alien Higgs-3/4, Monza 4/ 4QT/5
Antenna Material	Aluminium
Read Range	10 – 15m (Reader Dependent)
Label Size	30mm *12mm
EPC Memory	96/128 Bit
Write endurance of IC	100,000 cycles
Antenna Size	90mm X 24mm
Operating Temperature	-40 °C/ + 80 °C
Adhesive	3M Adhesive
Packing	Roll

PRODUCT USE IN THE SECTORS



ASSET TRACKING EXPRESS DELIVERY LOGISTICS WAREHOUSE MANUFACTURING

VEHICLE TRACKING FILE TRACKING JEWELLERY TRACKING

