

### DESCRIPTION:

DSPL (DSL-USG602) UHF RFID Security Gate integrated with the UHF security module, support by the EPC global Gen 2 and ISO18000-6C standard multivendor electronic tags, support to detect any EPC code number mode, max up to 3 doors installed in the same entrance. The identification distance of the channel is over 90cm (the identification distance is related to the performance, size of the tags, the site environment, etc.). This product can be widely used in the library/archive room and in importing and exporting anti-theft and other fields.

### RFID SECURITY GATE



### FEATURES:

- Visual and audible alarms at unauthorised item being taken out.
- Innovative security system ensures a high level of protection.
- Industry-leading read range.
- Available in single-lane and multiple-lane options.
- Anti-collision feature.
- Most modern detection algorithm that constantly detects any unauthorised item removal.
- Covers approximately 1-meter-wide pathway with no orientation limits.
- Inbuilt anti-collision algorithm.

### TECHNICAL SPECIFICATIONS:

Technology / Frequency	UHF RFID / 840-960MHz
Protocol	EPC global Gen 2 and ISO 18000-6C
Dimension (L*W*H) in mm	1663*630*118
Voltage	AC 100~240V 95mA 50~60Hz
Detection Width	Up to 120cm
Communication Interface	Ethernet
Material	Acrylic and sheet metal
Alarm System	Multi Colour Visual and Audible
Volume	Adjustable
Adjustable RF Power	1-30dBm

### PRODUCT USE IN THE SECTORS



ASSET TRACKING    EXPRESS DELIVERY    LOGISTICS    WAREHOUSE    MANUFACTURING

VEHICLE TRACKING    FILE TRACKING    JEWELLERY TRACKING    ANIMAL TRACKING

